

Convinient Induction Self Ballasted Bulbs for use in Commercial Applications



Endless Possibilities

Self Ballasted Bulbs

Up to 75% in energy savings



23Watt self ballasted Induction Bulb

85 CRI /
With the Lumen equivalency of the following:
150 watt Incandescent Bulb,
70 watt HPS (21CRI)Bulb,
50 watt MH (65CRI) Bulb

Avail. 120v, 277v
3000k,5000k color temperatures
Medium Base
Self-Ballaated
M.O.L. 7"
2.5" Width @ base of bulb
3" Width @ top of bulb

B23120CW	23 Watt / 120v / 5000k
B23120WW	23 Watt / 120v / 3000k
B23277CW	23 Watt / 277v / 5000k
B23277WW	23 Watt / 277v / 3000k

40Watt self ballasted Induction Bulb

85 CRI /
With the Lumen equivalency of the following:
250 watt Incandescent Bulb,
120 watt HPS (21CRI)Bulb,
85 watt MH (65CRI) Bulb

Avail. 120v, 277v
3000k,5000k color temperatures
Medium Base
Self-Ballaated
M.O.L. 9.75"
3.25" Width @ base of bulb
4.25" Width @ top of bulb

B40120CW	40 Watt / 120v / 5000k
B40120WW	40 Watt / 120v / 3000k
B40277CW	40 Watt / 277v / 5000k
B40277WW	40 Watt / 277v / 3000k

Product Features

Makes for a Safer and Brighter Enviroment
60,000 Hours Of Long Life
5 Year Warranty
No flickering, No Strobging, No Noise
Instant On Capability
Retro- fit Existing Fixtures

Cold Start At temperatures Of -40 Degrees Farenheit
Color Rendering 85 CRI
Color Temperature 3000k - 5000k
Ballast Replacement NOT Required (REMOVE OLD BALLAST)
Go 10 to 20 years without changing a bulb
Drasticy reduce your maintanence costs